



10

MIX Sarl Z.A de l'Avenir - Le Devois - 30600 VESTRIC & CANDIAC Tel: +33 (0)466 711 447 Fax: +33 (0)466 711 643

aplast



Sheet4MAGIC STAPLERSheet5PLASTIC REPAIR KITSheet6STAPLE BOXSheet7STAPLESSheet8TWO COMPONENT CARTRIDGES

plast

- Sheet 9-10 COMPLEMENTARY

Sheet	11	DISPENSING GUNS
Sheet	12	STATIC MIXERS
Sheet	13	SURFACE PREPARATION
Sheet	14	UNIVERSAL PRIMERS
Sheet	15	TEXTURISED PLASTIC PAINT
Sheet	16	SEALING TAPE



cplast line

Polyurethane Modified epoxy Plastic primer Plastic paint Magic Stapler

A whole product range Experience and innovation Tested and approval working steps



Mixplast[®] line

3660

MAGIC STAPLER

- -1 x 366(-) Welding gun with battery
- -1 x 36891 Semi-rigid modified epoxy 50 ml
- 1 x 3653 Moldable adesive Patch
- -1 x 3650 Wire mesh
- 10 x 3641 U shape staple
- 10 x 3642 V shape staple
- 10 x 3643 N shape staple
- -1 x 3644 Welding tip
- 10 x 3645 Staple 0.78 inch
- 10 x 3646 W shape staple
- 10 x 3647 M shape staple
- -1 x A3660 Battery charger



Magic Stapler is totally portable, powered by the latest generation Minh battery, driven by a current generator and controlled by a microprocessor that carefully manages the temperature according to the chosen cycle. This management allows to guarantee a working precision with an excellent speed on different model of staple and the use of the welding tip to melt wire mesh into plastic.









Mixplast[®] line

3007B

INTRODUCTORY KIT 200 ml

3608N -2 x Semi-rigid PU cartridge 3689N Semi-rigid Modified epoxy cartridge - 1 Х Surface modificator x 3604S - 1 x 36021 Plastic prep. cleaner - 1 x 3601N Static mixer big - 6 36012N Static mixer small - 6 Х 3633 Water born surfacer - 1 Х x 4903 Contouring film - 1 4904 Reinforcing film Х - 1 3600 High quality dispensing gun х - 1

3007ECO introductory kit200 Ml Idem with dispensing gun ECO 3600A



"Nous avons aussi une solution" pour tous les domaines





Mixplast[®] line

364SB		STAPLE BOX
3641 3642 3643 3645 3646 3646 3647 36891	X X X X X	 100 U shape staple 100 V shape staple 100 N shape staple 50 Staple 0.78 inch 50 W shape staple 50 M shape staple 1 Semi-rigid cartrige 50ml.




Strength and speed are the objectives of the new range of staples. The Staple box includes our latest version of Semi-rigid modified epoxy, for use directly onto plastics No PRIMER and No MIXERS needed.





Mixplast[®] line



SIMPLE STAPLES

U - V and N shape staple. Designed for small repairs, when normal resistance is required on non painted cosmetic fnishes. Perfect results on brackets, bumper rings, trims etc...

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Wire thickness:	0.031 Inch	3641	Bag	100	30
Wire quality:	Inox	3642	Bag	100	30
Resistance:	Good	3643	Bag	100	20

3645



HIGH RESISTANCE STAPLE

Staple 0.79 inch, extremely strong, designed for all interior and exterior repairs with cosmetic or not cosmetic paint finishes. Allows the repaired part to remain strong and maintain the original flexibility.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Wire thickness:	0.035 Inch	3645	Bag	50	12
Wire quality:	Inox				
Resistance:	Excellent				

3646	3647

DOUBLE STAPLE

M and W shape staple. Very strong, designed for all interior and exterior repairs with cosmetic or non cosmetic paint finishes. Allows the repaired part to remain strong and maintain the original flexibility.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Wire thickness: Wire quality: Resistance:	0.031 Inch Inox Very good	3646 3647	Bag Bag	50 50	24 24

3644



WELDING TIP

Designed to melt 3650 wire mesh, 3651 brazing fiber flex into plastic and to mix plastic over the staple for better cometic finishing.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Quality:	Specific laser cutted steel	3644	Bag	1	-



Mixplast[®] line

3608N





36081



36082

STRUCTURAL REPAIR SEMI RIGID PU

Two component polyurethane black in colour for structural repairs and plastic bonding application. Designed to be used with IR lamp for best result. Must be over spread with orange modified epoxy 3689.

Bond on PP/EPDM, ABS, XENOY, TPO, PUR

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Working time: Adhesive sandability Mixer needed:	1 minute 30 mn à 20°C 10 mn with IR Yes	3608N 36081 36082	Cartridge Cartridge Seringue	200ml 50ml 20ml	12 12 12
Cleaner - primer:	Yes				

3689N

36891

36892

REPAIR AND FINISHING CREAM SEMI RIGID EPOXY



Two component modified epoxy orange in colour for repairs and finishing cream on plastics. Designed to be painted, it eliminates all risks of chimical reaction and air buble that can appears during the paint process. It can be used with IR lamp for best result and over spayed with 3633 waterborn primer or whatever solvent primer.

Bond on PP/EPDM, ABS, XENOY, TPO, PUR Packaging Qty per Code Packaging Characteristic per box Packaging Working time: 1 minute 3689N Cartridge 200ml 12 36891 Cartridge 50ml 12 Adhesive sandability 30 mn à 20°C 10 mn with IR 36892 Seringue 20ml 12 Mixer needed: No Primer: No

3607N

36072





36071



CLEAR BONDING FLEXIBLE ADHESIVE PU

Two component urethane structural adesive clear in colour for bonding plastics and primed or painted metals. Designed for bonding emblems, body side moldings, plastic baker panels, decorative vents, wheel, bumper tabs, arilic sun visors, ... UV resistant.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Working time: Temps avant manipulation: Mixer needed: Primer:	1 minute 10 min à 20°C Yes Yes onto plastic	3607N 36071 36072	Cartridge Cartridge Seringue	200ml 50ml 20ml	12 12 12



Mixplast[®] line



Wire mesh 3650 is designed to repair holes from the outside on thermo-plastic parts. Melted with the Magic Stapler and its welding tip, it allows to create a strong support for the filling step with 3689 for small repairs or 3608 + 3689 for big holes.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Wire thickness: Mesh opening:	0.32 mm 1 mm	3650	Bag	2 mesh	12
Wire quality: Dimension:	Inox 120 x 250 mm				

3653

MOLDING ADESIVE FAST PATCH



AST PATCH is a technologicaly advanced, self adhesive repair material designed to quickly repair tears, holes and other damage to plastic parts. When heat is applied to the patch, it can be formed into the shape of the repair area. Once cool, the patch material hardens into its new shape to provide additional support to the repair. The net result is a stronger repair with superior peel resistance. Filling process must be done with 3608 and finishing with 3689.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Thickness: Dimension:	2 mm 204 x 101 mm	3653	Bag	1	12

3651

UBIVERSAL BRAZING FIBER FLEX



FIBER FLEX is used on small repairs to fill after the repair with Magic Stapler mesh or staple. After the cooling down you must use 3689 as finishing cream before the paint process.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Thickness: Dimension:	2.5 mm 290 x 210 mm	3651	Bag	10 Mesh	12





29X21

CLONE MAKER



Special plasticine reusable, designed to reproduce missing parts. It allows to take a perfect mold and doesn't stick with 3608 or 3689 two component after filling.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Thickness: Dimension:	2.5 mm 290 x 210 mm	29X21	Bag	2 sheets	1

571/HSS V SHAPE TOOL

Special drill designed to open the break and create a V shape. Allows to grind material without applying extra heat onto plastic.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Small diameter: Big diameter:	4 mm 6 mm	571/HSS	Box	1 drill	5



Mixplast[®] line

3600

HIGH QUALITY DISPENSING GUN



High quality Mixpack gun for 200 ml cartridges equiped with the stop flow system. Build in Aluminium, PP, PA6 and PBT. Important strong reducing, it offers an excellent ease of work.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Utilisation: Ratio: Weight:	Cartridges 200 ML 1:1 2:1 4:1 10:1 0.95 Kg	3600	Unit	1	1

3600A

STANDARD DISPENSING GUN 200ML



Mixplast gun for 200 ml cartridges, build in metal and alloy.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Utilisation: Ratio: Weight:	Cartridges 200 ML 1:1 1.5 Kg	3600A	Unit	1	1

3600C

MIXPLAST DISPENSING GUN 50ML




Mixplast gun for 50 ml cartridges, build in plastic.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Utilisation: Ratio: Weight:	Cartridges 50 ML 1:1 0.245 Kg	3600C	Unit	1	1



Mixplast[®] line



STATIC MIXER 200ML

Patented high efficiency mixers for 200ml cartridge applications. Used with 3607 - 3608 - 3689.

Code	Packaging	Qty per Packaging	Packaging per box
3601N	Bag	12	12
36012N	Bag	12	12


36011N



STATIC MIXER 50ML

Patented high efficiency mixers for 50ml cartridge applications. Used with 36071 - 36081 - 36891.

Code	Packaging	Qty per Packaging	Packaging per box
36011N	Bag	12	12



SCREW STATIC MIXER 200 ML

Mixers for 200 ml. cartridge applications.

Code	Packaging	Qty per Packaging	Packaging per box
3601	Bag	12	12
36012	Bag	12	12

36011



TWIST LOCK STATIC MIXER 50 ML

Mixers for 50 ml. cartridge applications.

Code	Packaging	Qty per Packaging	Packaging per box
36011	Bag	12	12



Mixplast[®] line



SURFACE MODIFIER

3604(S) must be applied before the 3607 and 3608 repair. Available in can with integrated brush or in aerosol.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Reaction time: Colour: Application :	3 - 5 minutes Clear integrated brush or in aero- sol.	3604 3604S	Can Aerosol	150ml 400ml	12 12

36021



ADHESION PREP CLEANER

Designed to remove most of the plastic contamination during the repair process and before the paint steps. Because of water basis 36021 must be wiped and dryed properly.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Colour:	Milky	36021	Vaporis.	500ml	6
Application:	Vaporisator	36021-5	Can	5LT	1
Drying/evaporation:	Heat air gun	36021-25	Can	25LT	1

3633



WATER BORNE PRIMER 1 LT

3633 is designed to seal and to prime the repair before the paint step. Single component, fast drying and ready to use, it must be sprayed in several thin coats. Infra red lamp is recommended for best cosmetic result. Do not use with low temperature or high humidity without drying system.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Colour: Recommended thickness:	Light grey 100µ with 3 coats	3633	Can	1LT	6
Storage à 20°C:	12 months not opennned	Ready to	50-60μ	Clean 1.8 mm)
Keep in a dry/warm place (Do	not storage less than 5°C)	use	6-8M²/Lit	2-3 bar	





Mixplast[®] line



CLEAR BOND UNIVERSAL CLEAR PRIMER

Clear Bond Primer is a strong adhesion promoter based on particular polyolefin type resin with polymerization. It has high solvent resistance, water resistance and corrosion resistance. Clear Bond is designed to be used in wet to wet application. It bonds on many surfaces like: ABS, Aluminium, Chrome, Galvanised steel, Glass, Magnesium, Polypropylene, Stainless steel, Tile and ceramics.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Colour: Recommended thickness: Overcoatable after:	5 - 10µ 500		Can Aerosol	1 lit 400ml	6 12
		Ready	$ \begin{array}{c} $	Clean 1.8 mm 2-3 bar	



387

0125

3671

3671

Bumper plus



6-8M²/Lit

2-3 bar

Wet to wet

P360

Universal primer suitable for plastic, metals, light alloys, zinc plated steel sheets, featuring good adhesion even to difficult surfaces; both function wet-on-wet and sandable, it can be recoated directly with sanding primers, wet-onwet primers and finishing coats.

Characteristic		Code	Packaging	Qty per Packaging	Packaging per box
Colour: Recommended thickness: Overcoatable after:	Light grey 15 - 20µ dryed 15-20 Mn. à 20°C -65% UR	3671 3673	Can Aerosol	1 lit 400ml	6 6
		3616	15 - 20μ Clean		1 5 - 20' P280



Mixplast[®] line





BUMPER PAINT STRUCTURÉE PLASTIQUE

One-component product offering excellent adhesion to most of plastic surfaces used in car bumpers manufacturing (polypropylene, polycarbonate, ABS, Pocan, xenoy, rigid polyurethane, fiberglass reinforced polyester, etc. except for polyethylene and mixture containing this stuff). It features fast drying, high adhesion, excellent resistance to washing and weathering; semi-matt appearance like the original bumpers. It can be used as a finishing treatment or as adhesion primer.

Characteristic		Code	Colour	Packaging	Qty per Packaging	Packaging per box
Dry film appearance: Gloss: Recommended thickness: Touch free: Dry through: Over paintable:	Satin matt 15 - 20 Gloss 60° 50 - 100µ sec 30 Mn. à 20°C -65% UR 8 h. à 20°C -65% UR 4 - 6 h. à 20°C -65% UR	3619 3612 3615 3618 3611	FZL Black White FZL Tintable	Aerosol Can Can Can Can Can	400 ml $1 lit$	6 6 6 6 6 20 [°]

3616



THINNER FOR BUMPER PAINT

5-7M² Lit

5-15%

Code	Couleur	Packaging	Qty per Packaging	Packaging per box
3616	-	Tin	1 lit	12

2-3 bar



Sealing Tape



Mixplast[®] line



Patented Sealing tape used by many vehicle manufacturers on numerous vehicles.

Accurately replicating the OEM seam seal on many vehicles (not flat) and flexible enough to go around corners without cutting, Sealing tape gives an OEM result in no time.

Just spray on the primer, apply the tape and it's ready to paint immediately!

Characteristic			Code	Packaging	Packaging per box
	Sealing	tape d06 16m	080655	-	10
	Sealing	tape d08 16m	080656		10
	Sealing	tape d10 16m	080657		10
	Arch tape 12mm	x 1 mm x 5 mt	8080900		10
	Arch tape 12mm	x 2 mm x 5 mt	8080901		10
	Arch tape 12mm	x 3 mm x 5 mt	8080902	\bigcirc	10
	Arch tape 15mm	x 1 mm x 5 mt	8080903		10
	Arch tape 15mm	x 2 mm x 5 mt	8080904		10
	Arch tape 20mm	x 1 mm x 5 mt	8080905		10
	Half moon tap	e 8 mm x 9 mt	8080800	\bigcirc	10
	Half moon tape	10 mm x 9 mt	8080801		10
		Roller	120002		1

CLEAR BOND PRIMER (also used for Sealing tape)



3674

Characteristic	Code	Packaging	Qty per Packaging	Packaging per box
	3670 3674	Bidon Aérosol	1 lit 400ml	6 12
	Ready to use	o 5 - 10µ 6-8M²/Lit	Clean 1.8 mm 2-3 bar	∂ ∂ ∂ ∂ ∂ ∂ ∂ ∂ ∂ ∂